



Hose made in neoprene coated fiberglass with galvanised steel spiral, for suction of fumes and hot air.



SMOOTH SURFACES

\*\*\*



FLEXIBILITY

\*\*\*\*\*



ABRASION RESISTANCE

\*\*\*\*\*



TEMPERATURE RANGE

-50°C +150°C  
-58°F +302°F



CHEMICAL RESISTANCE

NEOPRENE



CRUSHING RESISTANCE

\*\*\*

Ø I.D.	Ø I.D.	Ø O.D.	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	BURSTING PRESSURE 23°C	VACUUM 23°C	COIL LENGTH	AVAILABILITY
inch	mm	mm	g/m	mm	bar	bar	m h2o	m	
	51	55	250	26	1.2	3.6	4.4	4	IN STOCK
	63	67	300	32	1.1	3.3	4	4	IN STOCK
	70	74	395	35	1.1	3.3	3.5	4	IN STOCK
	76	80	410	38	1	3	3.5	4	IN STOCK
	83	87	470	42	1	3	3	4	IN STOCK
	89	93	495	45	0.9	2.7	3	4	IN STOCK
	102	106	570	51	0.9	2.7	2.6	4	IN STOCK
	114	119	730	57	0.8	2.4	2.1	4	IN STOCK
	121	126	760	61	0.8	2.4	1.9	4	ON DEMAND
	127	132	805	64	0.8	2.4	1.7	4	IN STOCK
	140	145	885	70	0.8	2.4	1.5	4	ON DEMAND
	152	157	1050	76	0.6	1.8	1.4	4	IN STOCK
	178	183	1210	89	0.6	1.8	1.1	4	ON DEMAND
	203	208	1380	102	0.5	1.5	1.6	4	IN STOCK
	254	259	1650	127	0.4	1.2	0.45	4	IN STOCK
	305	310	2000	153	0.1	0.3	0.3	4	ON DEMAND

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.